



Overview

Model Name	APC Power-Saving Back-UPS Pro 1500, 230V, India
Includes	Telephone Cable , USB cable , User Manual , Warranty card
Standard Lead Time	Usually in Stock
Product Distribution	India

Output

Output Power Capacity	865 Watts / 1500 VA
Max Configurable Power (Watts)	865 Watts / 1500 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60 Hz +/-1 Hz
Output Frequency (sync to mains)	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Output Connections	(2) India 3-pin 6A (Surge Protection) , (4) India 3-pin 6A (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	India 3-pin 16A
Cord Length	1.52 meters
Input voltage range for main operations	160 - 280 V

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	7.2 hour(s)
Replacement Battery	APCRBC144
RBC Quantity	1
Replacement battery cartridge note	9Ah x 2 internal batteries

Communications & Management

Interface Port(s)	USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	680 Joules
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector) , Network line - 10/100/1000 Base-T Ethernet (RJ-45 connector)

Physical

Maximum Height	301.0 mm
Maximum Width	114.0 mm
Maximum Depth	382.0 mm
Net Weight	11.76 kg
Shipping Weight	13.19 kg
Shipping Height	381.0 mm
Shipping Width	229.0 mm
Shipping Depth	483.0 mm
Master Carton Units	2.0
Master Carton Weight	28.14 kg
Color	Black
SCC Codes	1073130426879 3

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

Conformance

Standard warranty	2 years repair or replace
-------------------	---------------------------

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs