Product datasheet Characteristics

BR1000G-IN

APC Power-Saving Back-UPS Pro 1000 with LCD, 230V, India



Overview

Model Name	APC Power-Saving Back-UPS Pro 1000 with LCD, 230V, India	:
Includes	Telephone Cable , USB cable , User Manual , Warranty card	
Standard Lead Time	Usually in Stock	
Product Distribution	India	

Output

Output Power Capacity	600 Watts / 1000 VA	
Max Configurable Power (Watts)	600 Watts / 1000 VA	
Nominal Output Voltage	230V	
Output Frequency (sync to mains)	50/60 Hz +/-1 Hz	
Output Frequency (sync to mains)	Line Interactive	
Waveform Type	Stepped approximation to a sinewave	
Output Connections	(2) India 3-pin 6A (Surge Protection), (4) India 3-pin 6A (Battery Backup)	

Input

Model Name	APC Power-Saving Back-UPS Pro 1000 with LCD, 230V, India	
Includes	APC Power-Saving Back-UPS Pro 1000 with LCD, 230V, India Telephone Cable , USB cable , User Manual , Warranty card Usually in Stock India 600 Watts / 1000 VA 600 Watts / 1000 VA 230V 50/60 Hz +/-1 Hz Line Interactive Stepped approximation to a sinewave (2) India 3-pin 6A (Surge Protection) , (4) India 3-pin 6A (Battery Backup) 230V 50/60 Hz +/- 3 Hz (auto sensing) India 3-pin 6A 1.52 meters 150 - 280 V Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof 7.4 hour(s) APCRBC144 1 nt USB	
Standard Lead Time	Usually in Stock	
Product Distribution	India	
Output		
Output Power Capacity	600 Watts / 1000 VA	
Max Configurable Power (Watts)	600 Watts / 1000 VA	
Nominal Output Voltage	230V	
Output Frequency (sync to mains)	50/60 Hz +/-1 Hz	
Output Frequency (sync to mains)	Line Interactive	
Waveform Type	Stepped approximation to a sinewave	
Output Connections	(2) India 3-pin 6A (Surge Protection), (4) India 3-pin 6A (Battery Backup)	
Input		
Nominal Input Voltage	230V	
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)	
Input Connections	India 3-pin 6A	
Cord Length	1.52 meters	
Input voltage range for main operations	150 - 280 V	
Batteries & Runtime		
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	
Typical recharge time	7.4 hour(s)	
Replacement Battery	APCRBC144	
RBC Quantity	1	
Communications & Manageme	nt	
Interface Port(s)	USB	

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	
Typical recharge time	7.4 hour(s)	
Replacement Battery	APCRBC144	
RBC Quantity	1	Ţ

Communications & Management

Interface Port(s)	USB	

Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	680 Joules
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector) , Network line - 10/100/1000 Base-T Ethernet (RJ-45 connector)

Physical

,		
Maximum Height	301.0 mm	
Maximum Width	114.0 mm	
Maximum Depth	382.0 mm	
Net Weight	11.35 kg	
Shipping Weight	12.77 kg	
Shipping Height	381.0 mm	
Shipping Width	229.0 mm	
Shipping Depth	483.0 mm	
Master Carton Units	2.0	
Master Carton Weight	27.2 kg	
Color	Black	

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

Conformance

Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs