

Product data sheet

Characteristics

BR1100CI-IN

APC Back-UPS 1100, 230V, BS546A, without auto shutdown software, India



Overview

Model Name	APC Back-UPS 1100, 230V, BS546A, without auto shutdown software, India
Includes	User Manual , Warranty card
Standard Lead Time	Usually in Stock
Product Distribution	Bangladesh , India , Sri Lanka

Output

Output Power Capacity	660 Watts / 1100 VA
Max Configurable Power (Watts)	660 Watts / 1100 VA
Nominal Output Voltage	230V
Nominal Output Voltage	Line Interactive
Output Connections	(2) India 2/3-pin 6A (Surge Protection) , (3) India 2/3-pin 6A (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	47 - 63 Hz
Input Connections	Indian/South African BS 546A
Cord Length	1.48 meters
Input voltage range for main operations	175 - 295 V
Input voltage adjustable range for mains operation	160 - 286V
Maximum Input Current	0 A
Input Breaker Capacity	0 A

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	1
Battery Slots Empty	0
Typical recharge time	10 hour(s)
Replacement Battery	APCRBC113
RBC Quantity	1

Communications & Management

Available SmartSlot™ Interface Quantity	0
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rating	441 Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector)

Physical

Maximum Height	222.0 mm
Maximum Width	132.0 mm
Maximum Depth	356.0 mm
Rack Height	0 U
Net Weight	11.0 kg
Shipping Weight	13.5 kg
Shipping Height	310.0 mm
Shipping Width	244.0 mm
Shipping Depth	450.0 mm
Master Carton Units	1.0
Master Carton Dimensions (Length x Width x Height)	12.2 inches
Master Carton Weight	13.5 kg
Color	Charcoal
SCC Codes	1073130425013 2
Units per Pallet	40.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-5 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB
Online Thermal Dissipation	180.000 BTU/hr

Conformance

Approvals	CE
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs