Product data sheet Characteristics

BX1100C-IN

APC Back-UPS 1100VA, 230V, without auto shutdown software, India



Overview

	1000 1100 1100 1100 110 110 110 110 110	
Model Name	APC Back-UPS 1100VA, 230V, without auto shutdown software, India	
Includes	User Manual , Warranty card	
Standard Lead Time	Usually in Stock	
Product Distribution	India	

Output

Output Power Capacity	660 Watts / 1100 VA	
Max Configurable Power (Watts)	660 Watts / 1100 VA	
Nominal Output Voltage	230V	
Output Frequency (sync to mains)	50 Hz	
Output Frequency (sync to mains)	Line Interactive	
Waveform Type	Stepped approximation to a sinewave	:
Output Connections	(1) India 2/3-pin 6A (Surge Protection), (4) India 2/3-pin 6A (Battery Backup)	

Input

Model Name	APC Back-UPS 1100VA, 230V, without auto shutdown software, India	
Includes	User Manual , Warranty card	
Standard Lead Time	Usually in Stock	
Product Distribution	India	
Output		
Output Power Capacity	660 Watts / 1100 VA	
Max Configurable Power (Watts)	660 Watts / 1100 VA	
Nominal Output Voltage	230V	
Output Frequency (sync to mains)	50 Hz	
Output Frequency (sync to mains)	Line Interactive	
Waveform Type	Stepped approximation to a sinewave	
Output Connections	(1) India 2/3-pin 6A (Surge Protection), (4) India 2/3-pin 6A (Battery Backup)	
	230V	
Nominal Input Voltage	230V	
Input Frequency	45 - 65 Hz (auto sensing)	
Input Connections	India 3-pin 6A	
Cord Length	1.52 meters	
Input voltage range for main operations	145 - 290 V	
Maximum Input Current	0 A	
Input Breaker Capacity	7 A	
Batteries & Runtime		
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	
Included Battery Modules	0	
Battery Slots Empty	0	
Typical recharge time	6 hour(s)	
RBC Quantity	0	

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte: leakproof	<u>.º</u> .c
Included Battery Modules	0	4
Battery Slots Empty	0	
Typical recharge time	6 hour(s)	ة. م
RBC Quantity	0	

Communications & Management

Available SmartSlot™ Interface Quantity	0
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating 255 Joules	
--------------------------------	--

Physical

1 Hysiodi		
Maximum Height	282.0 mm	
Maximum Width	132.0 mm	
Maximum Depth	259.0 mm	
Rack Height	0 U	
Net Weight	8.98 kg	
Shipping Weight	10.22 kg	
Shipping Height	394.0 mm	
Shipping Width	203.0 mm	
Shipping Depth	384.0 mm	
Master Carton Units	0.0	
Master Carton Weight	0.0 lbs	
Color	Black	
Units per Pallet	0.0	

Environmental

Littiioiiiioiitai	
Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

Conformance

Approvals	BIS Approved
Standard warranty	1 year repair or replace

Sustainable Offer Status

REACH	REACH: Contains No SVHCs